

Data Sheet: Steel 1.7131

(16MnCr5)

Alternative Designations

Standard	AFNOR	ANSI/AA	BS	JIS	SIS	UNE
Designation	16MC5	5115	527M20	SCR415	2511	16MNCr5

Details

It has high surface hardness and wear resistance with good machinability. With a tensile strength of 600MPa, it is ideal for the manufacturing of gears, worms, bushings and other machine components.

Key Features

High surface hardness • Wear resistance

Chemical Composition

Element	С	Si	Mn	Р	S	Cr
Percentage	0.14 –	0.4	1 -	0.025	0.035	0.8 –
	0.19		1.30			1.1

Mechanical Properties

Property	Yield strength	Ultimate tensile strength	Elongation	Hardness
	[MPa]	[MPa]	[%]	
Value	1000	600 - 1160	15	207



Physical Properties

Property	Value
Density [g/cm³]	7.7
Module of elasticity [GPa]	190 – 210
Electrical conductivity [m/Ω · mm²]	1.43
Coefficient of thermal expansion [K-1 · 10-6]	16
Thermal conductivity [W/m · K]	42.7
Specific heat capacity [J/kg · K]	477

Reference

Datasheets provided by Xometry contain materials sourced through trusted OEMs, material distributors, and databases. Please visit <u>Materialdatacenter.com</u> for further information on this material.